

WHAT IS CLAIMED IS:

Sub
a1

1. A compact personal token, comprising:
a USB-compliant interface releaseably coupleable to a host processing device
operating under command of an operating system;
- 5 a smartcard processor having a smartcard processor-compliant interface for
communicating according to a smartcard input and output protocol;
an interface processor, communicatively coupled to the USB-compliant
interface and to smartcard processor-compliant interface the interface processor
implementing a translation module for interpreting USB-compliant messages into
10 smartcard processor-compliant messages and for interpreting smartcard processor-
compliant messages into USB-compliant messages.
2. The apparatus of claim 1, wherein the interface processor emulates a
smartcard reader to the smartcard processor.
- 15 3. The apparatus of claim 1, wherein:
the host processing device comprises a virtual smartcard reader in
communication with the operating system, the virtual smartcard reader for emulating
a smartcard reader communicatively coupled to the host processing device and
20 including a communication module for packaging messages for transmission to the
personal token via the USB compliant interface according to a first protocol and for
unpackaging messages received from the personal token via the USB-compliant
interface according to the first protocol; and
the interface processor translation module unpackages messages from the host
25 processing device according to the first protocol and packages messages destined for
the host processing device according to the first protocol.

005790-061500

4. The apparatus of claim 3, wherein the virtual smartcard reader further comprises a bootup module for responding to an operating system bootup procedure with an indication that a smartcard reader is communicatively coupled to the host processor.

5

5. The apparatus of claim 3, wherein the virtual smartcard reader further comprises an answer-to-reset (ATR) module for providing an ATR message to the operating system in response to a reset message.

10

6. The apparatus of claim 3, wherein the virtual smartcard reader further comprises a reporting module for receiving and reporting the insertion of the personal token in a USB-compliant port communicatively coupled to the host processor and the removal of the personal token as a removal of a smartcard from a smartcard reader.

15

7. The apparatus of claim 3, wherein the virtual smartcard reader further comprises a protocol selection module for receiving a protocol type selection (PTS) command from the operating system and providing a PTS response message to the operating system.

20

8. A host processing device, comprising:
a processor;
a memory, communicatively coupled to the processor, the memory storing processor operation commands implementing an operating system; and
25 a virtual smartcard reader module stored in the memory and in communication with the operating system, for emulating at least one smartcard reader to the operating system.

9. The apparatus of claim 8, wherein the virtual smartcard reader module comprises a communication module for packaging messages for transmission to a personal token communicatively coupled to the host processor via a USB-compliant interface and for unpacking messages received from the personal token.

5

10. The apparatus of claim 8, wherein the virtual smartcard reader comprises a bootup module for responding to an operating system bootup procedure with an indication that a smartcard reader is communicatively coupled to the host processor.

10

11. The apparatus of claim 8, further comprising an answer-to-reset (ATR) module providing an ATR message to the operating system in response to a reset message.

15

12. The apparatus of claim 8, wherein the virtual smartcard reader further comprises a reporting module for receiving and reporting the insertion of a personal token in a USB compliant port communicatively coupled to the host processor and the removal of the personal token as a removal of a smartcard from a smartcard reader.

20

13. The apparatus of claim 8, wherein the virtual smartcard reader further comprises a protocol selection module for receiving a protocol type selection (PTS) command from the operating system and providing a PTS response message to the operating system.

005456-061500

14. A method of communicating with a smartcard processor in a personal key communicatively coupled to a host computer via a USB-compliant interface, comprising the steps of:

accepting a message comprising a smartcard reader command selected from a smartcard reader command set from a host computer operating system in a virtual smartcard reader;

packaging the message for transmission via a USB-compliant interface according to a first message transfer protocol;

transmitting the packaged message to a personal key communicatively coupled to the USB-compliant interface;

receiving the packaged message in the personal key;

unpackaging the message in the personal key to recover the smartcard reader command;

translating the smartcard reader command into a smartcard command within the personal key; and

providing the smartcard command to the smartcard processor.

15. The method of claim 14, further comprising the steps of:

accepting a smartcard response from the smartcard processor;

translating the smartcard response into a smartcard reader response;

packaging the smartcard reader response for transmission to the host processor via the USB-compliant interface;

transmitting the packaged message from the personal key to the host processor;

receiving the packaged message in the host computer;

unpackaging the smartcard reader response; and

providing the smartcard reader response to the host processor operating system.

16. The method of claim 14, further comprising the steps of:
accepting a startup query from the host computer operating system in the
virtual smartcard reader; and
providing an indication that a smartcard reader is communicatively coupled to
5 the host computer to the host computer operating system.

17. The method of claim 16, further comprising the steps of:
receiving an indication that the personal key has been communicatively
coupled to the USB-compliant interface;
10 reporting the indication that the personal key is communicatively coupled to
the USB-compliant interface to the host processor operating system as the insertion of
a smartcard;
receiving an indication that the personal key has been communicatively
decoupled from the USB-compliant interface; and
15 reporting the indication that the personal key has been communicatively
decoupled from the USB-compliant interface to the host processor operating system
as the removal of the smartcard.

18. The method of claim 14, further comprising the steps of:
20 receiving a protocol type selection (PTS) command from the host computer
operating system; and
providing a PTS response message to the operating system.

005790" 9546560

19. A virtual smartcard reader emulator system, comprising:
- a first smartcard reader emulator, implemented in a host computer for emulating smartcard reader operations to the host computer; and
 - a second smartcard reader emulator, implemented in a personal key, for
- 5 emulating smartcard reader operations to a smartcard-interface compliant personal key processor.

005790-954456-061500